



SERVICE | EXCELLENCE | VALUE | EFFICIENCY

HM-Series Washer

HM-Series Industrial Washer Extractors

The SEVE HM series of washer extractors are hard mounted machines and feature heavy-duty construction for low and medium speed extraction without the need for a suspension system.

Available with electric or steam heating, SEVE HM washers are equipped with a fully programmable computer controller as standard, together with fully-stainless steel construction for resistance to corrosion and a long service life.



Key Features

- Fully programmable computer controller.
 - LCD display for easy-to-read program and status information.
 - Compatible with automatic liquid chemical dosing system.
 - Variable and programmable extraction speeds.
 - Inverter drive technology affords smooth operation and enhanced service life.
 - Efficient drum and sump design reduce energy, water and chemical consumption.
-
- | | |
|-------------------|----------------------|
| • Colour: | Stainless Steel |
| • Capacity (kg): | 15, 20, 25, 35 or 55 |
| • Heating Source: | Electric or Steam |
| • Power Supply: | 380v/50Hz/3Ph |
| • Warranty: | 1-Year |

Technical Specifications

Models	HMS15	HMS20	HMS25	HMS35	HMS55
Rated Load (kg)	15	20	25	35	55
Cylinder Size	400 x Ø700	520 x Ø700	540 x Ø750	490 x Ø955	700 x Ø955
Wash Speed (rpm)	50	50	38	36	36
Extraction Speed (rpm)	580	580	570	570	570
Motor Power (kW)	1.5	2.2	3	5.5	7.5
Heating Power (kW)	12	12	21	24	36
Water Inlet (in)	¾	¾	1	1	1
Drain Outlet (mm)	Ø75	Ø75	Ø75	Ø75	Ø75
CONSUMPTION PER CYCLE *					
Water (l)	38	48	63	84	134
Electricity (kWh)	0.53	0.63	1.05	1.46	2.29
DIMENSIONS					
Width (mm)	870	870	1000	1200	1200
Height (mm)	1360	1360	1460	1700	1700
Depth (mm)	820	920	1240	1310	1480
Net Weight (kg)	220	240	530	960	1030

* Cold water temp. 15°C and hot water temp. 60°C.

Due to continuous product improvements, design and specifications are subject to change without prior notice. E & OE.