



SERVICE | EXCELLENCE | VALUE | EFFICIENCY

DC-Series

DC-Series Dry Cleaning Perc. or Multi-Solvent

SEVE DC-Series dry cleaning machines employ advanced soft-mount design and are manufactured to the highest quality. Many enhanced features are standard, such as high-speed extraction, dual water separators and large distillation capacity. Further enhancing the appeal with durability and long service life is the comprehensive use of stainless steel. Components such as the solvent tanks, wash drum, distillation tank, water separators, filters and piping are all produced in corrosion-resistant stainless steel.

Key Features

- High-speed extraction up to 500G.
- Easy-to-use touch-screen interface.
- Dual water separators
- Ecological, Carbon and Lint Filtration.
- Heavy-duty stainless steel construction.
- Available in Perc. or Multi-Solvent version.

Essential Data

- Colour: White
- Capacity (kg): 10, 15, 27
- Heating Source: Electric or Steam
- Power Supply: 380V/50Hz/3N
- Warranty: 1-Year



Technical Specifications

Models	DCP10	DCP10 Slim	DCP14	DCP26		DCM10	DCM10 Slim	DCM14	DCM26
Capacity	10	10	14	26		10	10	14	26
Cylinder Volume (l)	203	203	273	527		203	203	273	527
Washing Speed (rpm)	30 - 40					30 - 40			
Extraction Speed (rpm)	990		900			990		900	
Tanks	3					3			
Tank Volume									
Tank 1 (l)	122	110	169	236		122	110	169	236
Tank 2 (l)	122	110	169	236		122	110	169	236
Tank 3 (l)	120	121	215	287		121	121	215	237
Distillation Tank (l)	140	140	231	374		144	144	230	396
Filtration									
Carbon Filter	Yes					Yes			
Filter Discs	30					30			
Filter Volume (l)	59					59			
Electrical Power									
Distillation Elements (kW)	6.9		8.4	n/a		6.9		8.4	n/a
Drum Motor (kW)	4		5.5	11		4		5.5	11
Drying Elements (kW)	6.9		8.4	n/a		6.9			n/a
Fan Motor (kW)	1.5			2.2		1.5			2.2
Filter Motor (kW)	0.2					0.12			
Refrigeration Compressor (kW)	2.6		4.5	6.6		2.6		4.5	6.6
Solvent Pump (kW)	0.75			1.1		0.75			1.1
Connections									
Electrical (v/Hz/Ph)	380/50/3					380/50/3			
Air (mm)	ø8					ø8			
Steam Inlet/Outlet (mm)	15	15	20	20		15	15	20	20
Water Inlet/Outlet (mm)	20	20	25	25		20	20	25	25
Pressures									
Air (bar)	4 ~ 6					4 ~ 6			
Steam (bar)	4 ~ 5					4 ~ 5			
Water (bar)	2 ~ 4					2 ~ 4			
Dimensions									
Width (mm)	1540	980	1950	2300		1540	980	1950	2300
Depth(mm)	1460	2050	1718	1905		1460	2050	1718	1905
Height (mm)	1948	2000	2247	2380		1948	2000	2247	2380

Due to continuous product improvements, design and specifications are subject to change without prior notice.